

IN USE WORLDWIDE



KLEENOIL FILTRATION INDIA PVT. LTD.

KLEENOIL®

www.kleenoilindia.com

OIL SKIMMER



Before
KLEENOIL Filtration



After
KLEENOIL Filtration



GeM
Government
e Marketplace

OIL SKIMMER

Our belt oil skimmer efficiently removes oil from the surface of oily effluent. It works on the principle of the difference in surface tension of oil and water. A rotating endless lyophilic belt passes through the oily effluent, which breaks the surface tension of the water to attract and collect the floating oil. The belt is passed through a set of wiper blades where the oil is wiped off from both sides of the belt.

Salient Features:

- ✓ Belt Skimmer
- ✓ High-quality aluminium case
- ✓ Oil-feeding special belt
- ✓ Construction requires little space
- ✓ Low priced system
- ✓ Simple and low-cost operation

Application:

- ✓ Grinding
- ✓ CNC
- ✓ VMC
- ✓ Hobbing

Removes floating leakage oil from the tank surface.
High-performance oil skimmer for continuous operation.

Output	Approx. 4 l/h
Bandwidth	40 mm
Max. immersion depth	1500 mm
Power unit	110 V / 220 V
Casting size	155 x 85 x 148 mm
Weight	1.8 kg



Oil Skimmer attached to a grinding machine

Contact us:

KLEENOIL FILTRATION INDIA PVT.LTD

537, Udyog Vihar Phase 5, Gurgaon (Haryana) 122016

Helpline: +91 9899151010, Board: +91 124 4904545

Email: info@kleenoilindia.com Website: www.kleenoilindia.com